



Optional accessories shown on vehicle

THE NEW WORK UTV STANDARD

The PRO XD provides industry-leading durability, serviceability and safety to deliver a utility vehicle built to withstand the toughest work environments, and ultimately, provide customers with increased durability, lower maintenance costs and improved safety features.



DURABILITY

- Heavy-duty driveline components resist corrosive conditions
- Heavy-duty suspension for industry-leading towing and payload
- Kubota® industrial tier 4 diesel engine
- Heavy duty seat material resists punctures and tears
- Heavy-duty clutch improves belt life
- Hard surface jobsite tire for puncture and wear resistance



SERVICEABILITY

- 200 hour maintenance interval
- Front air intake for cleaner air ingestion
- Side access to air filter and dipstick for daily service checks
- Digital display with alarms to notify user of critical faults
- 4 same size tires, non-directional for easy replacement
- Common key sets for easy vehicle fleet management



SAFETY

- Speed limited for jobsite compliance
- Orange seat belts and decals for high visibility
- Wider foot wells for easier ingress/egress
- Standard safety features include
 - Backup alarm
 - Horn
 - Mechanical parking brake
 - Start in park with foot on brake

4000D SPECIFICATIONS

4
Passenger
Capacity

200 Hour
Maintenance
Intervals

26 MPH
Top
Speed

Engine & Drivetrain	
Cooling	Liquid
Cylinders Placement	898 cc
Horsepower	24.5 HP
Drive System Type	AWD - Ultra Turf
Engine Braking System (EBS)	Standard
Engine Type	3-cylinder Kubota® Diesel
Fuel System/Battery	Mechanical Injection
Transmission/Final Drive	Automatic PVT H/L/N/R/P; Shaft
Maintenance Interval	200 Hours (50 Hour Initial)
Air Intake	Front Air Intake with Donaldson® Cyclonic Air Filter
Dimensions & Capacity	
Bed Box Dimensions (LxWxH)	43.5 x 54 x 11.5 in (110.5 x 137 x 29 cm)
Estimated Dry Weight	1,925 lbs
Box Cargo Capacity	1,250 lbs
Fuel Capacity	11.5 gal (43.5 L)
Ground Clearance	11 in
Overall Vehicle Size (LxWxH)	157 x 62.5 x 75 in
Towing Capacity	2,500 lbs
Payload Capacity	2,075 lbs
Person Capacity	4
Wheelbase	117 in
Brakes	
Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers
Parking Brake	Park in Transmission + Separate Mechanical Parking Brake Standard
Additional Specifications	
Top Speed	26 mph, 15 mph speed kit optional
Cargo System	Lock & Ride®
Front Suspension	9 in
Hitch Towing Rating	2,500 lb (1,133.9 kg)
Hitch Type	Standard 2 in (5 cm) Receiver
Instrumentation	All Digital Gauge, Speedometer, Odometer, Tachometer, 2 Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, Engine Temperature, Hi-Temp Light, Clock, Clutch Belt Slip Warning, Glow Plug Indicator, Low Oil Pressure Indicator, Seat Belt Indicator, Parking Brake Engaged Alarm
Lighting	55W low / 60W high, LED Tail
Other Standard Features	Horn, Backup Alarm
Rear Suspension	9 in
Tilt Steering	Standard
Seat Covering	Heavy-Duty Vinyl (Grey)
Tires/Wheels	
Electronic Power Steering	Standard
Front Tires	26 x 10-12 Duro® DI-2042 Power Grip (M/T)
Rear Tires	26 x 10-12 Duro® DI-2042 Power Grip (M/T)
Wheels	12 x 6 HD Steel - Gloss Black
Hubs	Front: Steel; Rear: Ductile Iron



For more information or to find out how Polaris PRO XD's industry-leading durability, serviceability and safety can impact your fleet's productivity, contact one of our UTV experts today.

POLARIS.COM/COMMERCIAL

Warning: Polaris PRO XD vehicles can be hazardous to operate and are not intended for on-road use. All riders should always wear head protection – such as hard hats or a helmet – that is appropriate for operating conditions and intended usage, considering factors such as intended speed, unevenness of terrain, turns in path, weather, obstacles, and other traffic. Always use seat belts and close doors (as equipped). Never engage in stunt driving, and avoid excessive speeds and sharp turns. Riding and alcohol/drugs don't mix. All riders should take a safety training course. Call 800-342-3764 for additional information.

Unless noted, trademarks are the property of Polaris Industries Inc. Donaldson® is a registered trademark of Donaldson Company, Inc. Duro® is a registered trademark of HWA Fong Rubber (USA) Inc. Kubota® is a registered trademark of Kubota Corporation. (Kevlar® is a registered trademark of E.I. du Pont de Nemours & Company).©2019 Polaris Industries Inc